



PURA® Ultraviolet Disinfection & Filtration Products

PURA® is an advanced Ultraviolet Water Treatment System. It has been designed with you, the consumer, in mind. PURA® Products are lightweight, easy to use and simple to maintain. PURA® Products will provide you with clean, disinfected drinking water for years to come.

All PURA® products feature:

- Water disinfection
- Easy to change lamp and filters
- Simple installation
- Lamp and ballast matched for quality assurance



Disinfection and filtration all-in-one.

Pure® Water Treatment Systems

PURA® Water Treatment Systems



UV1-EPCB Series™

PURA® Product's UV1-EPCB Series™ is a bright example of PURA® Product's patented All-In-One concept. This product combines both ultraviolet disinfection with carbon filtration all in a very attractive and compact system. The UV1-EPCB Series™ is rated for 1 gallon per minute and uses either a 0.5 micron (EPCB) carbon block filter or a 10 micron (EPCB 10) carbon block filter (optional). This easy to install system can be used as a stand alone or in conjunction with other water treatment products.

Features:

- Compact size
- Standard voltage 115V

Options:

- 220V / 50 Hz
- 12V DC
- Carbon block 10 micron (EPCBX)



UVB Series™

PURA® Product's patented UVB Series™ is designed to provide disinfected water at a flow rate of 2 gallons per minute. In addition to disinfection, water is filtered through our 0.5 micron Extended Pass Carbon Block (EPCB) filter.

Our double and triple models provide you with additional filtration with sediment and activated carbon filters.

This compact All-in-One system installs with ease and can be used anywhere that clean, clear, good tasting disinfected water is needed. It is ideal for point-of-use applications like: under the kitchen sink, office water coolers, water vending machines, boats, recreational vehicles, etc.

Features:

- Electronic lamp indicator (LED)
- Standard voltage 115V

Options:

- 220V / 50 Hz
- 12V DC
- Lamp out Circuit (LOC) Safety Monitor for: Alarm or Solenoid shutoff



UV20 Series™

PURA® Product's UV20 Series™ is designed to provide disinfected water at a flow rate of 8 - 10 gallons per minute. This system is ideal for whole house water treatment. In addition to disinfection, the double and triple models provide filtration for the removal of sediment and chemical contaminants. This ultraviolet water treatment system makes a perfect companion to water softeners, distillers, reverse osmosis and ozone systems. The UV20 Series™ has proven to be PURA® Product's most popular product line and has created an industry standard in whole-house disinfection.

Features:

- Electronic lamp indicator (LED)
- Standard voltage 115V

Options:

- 220V / 50 Hz
- 12V DC
- Lamp out Circuit (LOC) Safety Monitor for: Alarm or Solenoid shutoff



UV ADDON Series™

PURA® Product's UV ADDON Series™ is designed to be an easy addition to water treatment systems that require ultraviolet disinfection (RO systems, holding tanks, water dispensers, recirculating systems and more). The ADDON systems are available with a 1 GPM or 3 GPM flow rate. They are constructed using a 304 grade stainless steel body with a molded head that includes 3/8" quick connect fittings on the inlet/outlet. This versatile system also includes a heavy duty mounting bracket, but will also fit standard 2" RO mounting clips. The UV ADDON Series™ can be used almost anywhere and is equipped with a unique power supply that makes installation simple, space requirements minimal and lamp changes easy.

Features:

- Standard voltage 115V
- 3/8" quick connect fittings

Options:

- 220V / 50 Hz
- 12V DC



UV Big Boy™ Series

The UV BigBoy™ Series is the most versatile commercial ultraviolet disinfection system on the market today. This 15 to 60 GPM series is manufactured with versatility in mind, and is virtually unlimited in the possible filter configurations and manifold sequences. The series is designed with the same traditional style that PURA® has made an industry standard - worldwide.

One advantage of the UV BigBoy™ Series is the convenient manifold mounting rack. The rack can be used to configure up to four UV chambers in parallel or in series. This allows the user to achieve either a higher UV dosage or higher flow rate (up to 60 GPM). This mounting rack configuration provides easy access for cleaning and maintenance to the individual units without the need to shut down the entire water distribution line. The standard LED lamp monitor provides a visual verification the lamp is in operation.

The UV BigBoy™ Series, with its capacity, versatility and cost, is the world's most flexible, complete water disinfection system in its class.

Features:

- Electronic lamp indicator (LED)
- Standard voltage 115V

Options:

- 220V / 50 Hz
- 12V DC
- Bag Filters
- Lamp out Circuit (LOC) Safety Monitor for: Alarm or Solenoid shutoff



PURA® systems are guaranteed to be free from defects in materials and workmanship for a period of three years under normal use with the exception of electrical components which are guaranteed for a period of one year.

These systems are for the supplemental treatment of disinfected drinking water which has been treated or other drinking water which has been tested and deemed acceptable for human consumption by the state or local health agency having jurisdiction. These systems are designed to reduce normally occurring non-pathogenic nuisance organisms and is not intended for the treatment of contaminated water.

Specifications & Performance UV1 Series™

Model Description	# of sumps	Sump Type	Sump Content	Lamp #	Power Used	Flow Rates ⁽¹⁾ GPM	Dimensions Inches H x W x D	Shipping Weight Lbs.	Inlet/Outlet Size
UV1-EPCB	1	#10SL	EPCB Carbon/UV	#10	10 Watts	1	13.5 x 5.0 x 5.0	7.0	1/2" NPT

Specifications & Performance UVB Series™

Model Description	# of sumps	Sump Type	Sump 1	Sump 2	Sump 3	Lamp #	Power Used	Flow Rates ⁽¹⁾ GPM	Dimensions Inches H x W x D	Shipping Weight Lbs.	Inlet/Outlet Size
UVB1-EPCB	1	#10	EPCB Carbon/UV	none	none	#11	14 Watts	2	15 x 5.5 x 5.5	10.0	3/8" NPT
UVB2-EPCB/SD	2	#10	5 Micron Sed Filter	EPCB Carbon/UV	none	#11	14 Watts	2	15 x 11 x 5.5	15.0	3/8" NPT
UVB3-EPCB/GC/SD	3	#10	5 Micron Sed Filter	Granular Carbon Filter	EPCB Carbon/UV	#11	14 Watts	2	15 x 16 x 5.5	24.0	3/8" NPT

Specifications & Performance UV20 Series™

Model Description	# of sumps	Sump Type	Sump 1	Sump 2	Sump 3	Lamp #	Power Used	Flow Rates ⁽¹⁾ GPM	Dimensions Inches H x W x D	Shipping Weight Lbs.	Inlet/Outlet Size
UV20-1	1	#20	UV	none	none	#20	22 Watts	10	25 x 5.5 x 5.5	16.0	3/4" NPT
UV20-2 SD	2	#20	5 Micron Sed Filter	UV	none	#20	22 Watts	10	25 x 11 x 5.5	23.0	3/4" NPT
UV20-2 CB	2	#20	10 Micron Carbon Block	UV	none	#20	22 Watts	8	25 x 11 x 5.5	25.0	3/4" NPT
UV20-3 SD/CB	3	#20	5 Micron Sed Filter	10 Micron Carbon Block	UV	#20	22 Watts	8	25 x 16 x 5.5	33.0	3/4" NPT

Specifications & Performance UV BigBoy™ Series

Model Description	# of sumps	Sump Type	Sump 1	Sump 2	Sump 3	Lamp #	Power Used	Flow Rates ⁽¹⁾ GPM	Dimensions Inches H x W x D	Shipping Weight Lbs.	Inlet/Outlet Size
UVBB-1	1	#20BB	UV	none	none	#20	22 Watts	15	28 x 7.5 x 9.0	18.0	1-1/2" NPT
UVBB-2	2	#20BB	5 Micron Sed Filter	UV	none	#20	22 Watts	15	28 x 15 x 9.0	35.0	1-1/2" NPT
UVBB-3	3	#20BB	5 Micron Sed Filter	10 Micron Carbon Block	UV	#20	22 Watts	15	28 x 23 x 9.0	54.0	1-1/2" NPT

Specifications & Performance UV ADDON Series™

Model Description	# of sumps	Sump Type	Sump Content	Lamp #	Power Used	Flow Rates ⁽¹⁾ GPM	Dimensions Inches H x W x D	Shipping Weight Lbs.	Inlet/Outlet Size
UV Addon-1	1	304 SS	UV	#10	10 Watts	1	12 x 4 x 3.5	5.0	3/8" QC
UV Addon-3	1	304 SS	UV	#20	22 Watts	3	22.5 x 4 x 3.5	7.0	3/8" QC

Specifications & Performance UV BigBoy™ Rack Series

Model Description	# of sumps	Sump Type	Sump 1	Sump 2	Sump 3	Sump 4	Lamp #	Power Used	Flow Rates ⁽¹⁾ GPM	Dimensions Inches H x W x D	Shipping Weight Lbs.	Inlet/Outlet Size
UVBB-R1	4	#20BB	empty ⁽²⁾	empty	empty	UV	#20	22 Watts	15	45 x 34 x 18	65.0	1-1/2" NPT
UVBB-R2	4	#20BB	empty	empty	UV	UV	#20	44 Watts	30	45 x 34 x 18	75.0	1-1/2" NPT
UVBB-R4	4	#20BB	UV	UV	UV	UV	#20	88 Watts	60	45 x 34 x 18	91.0	1-1/2" NPT

Conditions For Use

Source Water Supply Profile		Chemical Parameters	Max mg/L
Feed Water Pressure ¹	20 – 75psig (138 – 517kPa)	Hardness (CaCO ₃)	< 120
Feed Water Temperature	38° – 105°F (3.3° – 40.5°C)	Iron (Fe)	< 0.3
pH Range	6.5 – 9.5	Manganese (Mn)	< 0.05
Total Dissolved Solids	< 1500 mg/L	¹ Water Pressure must not exceed 75 psig (517 kPa) or a pressure regulator must be installed.	
Total Suspended Solids	< 10 mg/L		
Turbidity	< 5 NTU		

Notes: a. ⁽¹⁾ All flow rates shown will provide a UV dose of no less than 16,000 µW-s/cm² or greater.

b. ⁽²⁾ Empty sumps on UVBB-Rack systems can be filled with a wide variety of optional cartridges.

c. EPCB refers to Extended Pass Carbon Block filter.

U.S. Patent #4,971,687



2880 - 45th Ave. SE, Unit 340, Calgary, AB T2B 3M1
265 Industrial Road, Cambridge, ON N3H 5N3

www.petwa.ca